



**ZETTEX**

STICK WITH US

## TECHNICAL DATA SHEET

### Easycontact S20

**Zettex Europe B.V.**

Plaza 20, 4782 SK Moerdijk

The Netherlands

+31 (0)888-93 88 39

[info@zettex.com](mailto:info@zettex.com)

[www.zettex.com](http://www.zettex.com)

#### Product description

Zettex Easycontact S20 is an extremely quick-drying universal contact adhesive suitable for most materials in construction and industry. Zettex Easycontact S20 can be applied with a brush or roller and is DCM-free.

#### Material

SBR Rubber

#### Advantages

- Extremely Fast drying
- Extremely powerful
- Mist spray
- For universal use
- Ready to use
- Barely penetrates porous materials

#### Uses

For the adhesion and fastening of paper, wood, cork, decorative film, foil and textile materials, insulation, PU, EPS, HPL, SKY and all kinds of leather or rubber.

#### Directions for use

Dry the materials to be adhered and remove dust and grease. This can be done with Zettex Profireinger. Then carefully apply the contact adhesive to both surfaces. A brush or a roller can be used here. Preferably apply the adhesive in rows without overlapping. After 2-4 minutes adhere both surfaces to each other and firmly press or roll. When there has been overlapping of the Easycontact S20 the open time must at least be doubled. With very porous surfaces carefully check whether there is sufficient contact between both adhesive layers. Apply an extra layer if this is required.

#### Available forms

Drum 1 kg, 2.5 kg, 5 kg, 10 kg, 25 kg, 50 kg, 200 kg and 1000 kg.

#### Colour

Transparent

#### Safety recommendations

This technical information does not contain an MSDS (Material Safety Data Sheet). You must first fully read the MSDS before using this product.

Properties	Specifications
Processing temperature	+5 to +40 degrees
Temperature resistance	-40°C to +100°C