



**ZETTEX**

STICK WITH US

## TECHNICAL DATA SHEET

### Spraybond X30 Canister

**Zettex Europe B.V.**  
Plaza 20, 4782 SK Moerdijk  
The Netherlands  
+31 (0)888-93 88 39  
[info@zettex.com](mailto:info@zettex.com)  
[www.zettex.com](http://www.zettex.com)

#### Product description

Zettex Spraybond X30 is a very high quality heatresistant contact adhesive for gluing EPDM, Rubber, TPO, HPL, wood and all types of synthetics (except PE and PP).

#### Material

SBR Rubber

#### Product properties

- Very powerful
- Heat resistant
- Extremely powerful
- Fast drying
- For universal use
- Ready to use
- DCM free

#### Areas of application

For gluing all types of EPDM (American and European) and almost all types of roof covering, on all surfaces. Spraybond X30 has various test certificates and has been approved under the new standards of the ATG and the EU directive on surface adhesives.

#### Applications

Remove any moisture and grease from the surface being glued. Gently spray the contact adhesive onto both surfaces being glued. The ideal distance between the surface and the spray gun is 30 cm. Try to apply the glue in a single layer. Bring the surfaces together after 2-4 minutes and press or roller firmly. Wait at least twice as long to glue the surfaces together if the layers applied have overlapped. Check thoroughly to see whether there is sufficient contact between the glue layers if the surface is porous. Apply an extra layer, if necessary.

#### Packaging

- Aerosol 500 and 750 ml.
- Pressurised cylinder 17 L

#### Colour

Amber/Blue/Red

#### Safety recommendations

Make sure you have read our MSDS (Material Safety Data Sheet) before using this product.

Properties	Specifications
Processing temperature	+5 to +40 °C
Temperature resistance	-40 to + 110 °C
Consumption	70-80 gram/m2
Open time	3-4 min
Maximum yield	140 m2

Solids	35%
Color	Amber/Blue/Red
Spray pattern	WEB
VOC	544 g/l