



ZETTEX
STICK WITH US

TECHNICAL DATA SHEET MOS2 Oil

Zettex Europe B.V.
Plaza 20, 4782 SK Moerdijk
The Netherlands
+31 (0)888-93 88 39
info@zettex.com
www.zettex.com

Product description

Zettex MOS2 Oil is a general-purpose lubricant and penetrant based upon refined naphthenic oil. This product also contains a residual solid lubricant that provides longer term protection, and a slightly increased viscosity on drying, with much enhanced surface slip properties ideal for anti-seize uses in assembly/disassembly work. Zettex MOS 2 easily resolves rust and salt on metal surfaces. Besides that, the MOS 2 Oil contains graphite.

Product benefits

- Enhanced reduction of frictional forces
- Enhanced durability
- Rapid penetration into rusted / corroded components

Applications

You can use the Zettex MOS2 Oil for all normal lubricant and ambient temperature anti-seize applications. Please don't use it on Plastics. Shake the aerosol before use. Hold upright, and spray from a distance of 20 to 30cm. Remove excess or overspray with a clean cloth where necessary.

Packaging

Aerosol 500 ml

Colour

Grey

Safety recommendations

Please read our MSDS before using this product.

Properties	Specification
Appearance	An opaque grey liquid
pH	Not applicable
Specific Gravity	0.805 +/- 0.015 at 20 degrees
Flammability, as supplied	Extremely flammable, flash point below -20
Composition Data	A solution of a naphthenic based lubricant, petroleum wax, Molybdenum disulfide in low aromatic white spirit in a butane/isobutane/propane propellant.
Non-Volatiles % m/m	20-30
Active content % m/m, as supplied	10-20
Service temperature (Continuous)	Designed for use at ambient temperatures