

according to 1907/2006/EC, Article 31

Page 1/12

Printing date: 30.04.2019

Version: 30

Revision: 30.04.2019

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

Trade name: Zettex Zinc Spray Galvaniser

**Article number:****1.2 Relevant identified uses of the substance or mixture and uses advised against****Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU21 Consumer uses: Private households / general public / consumers

**Product category** PC9a Coatings and paints, thinners, paint removers**Process category**

PROC7 Industrial spraying

PROC11 Non industrial spraying

**Application of the substance / the mixture** Spray varnish**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

Zettex Europe BV

Plaza 20, 4782 SK Moerdijk

The Netherlands

+31(0)888-938839

info@zettex.nl

www.zettex.nl

**1.4 Emergency telephone number:** +31(0)888-938839**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**

GHS02



GHS07



GHS09

(Contd. on page 2)

-GB-

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 30.04.2019

Version: 30

Revision: 30.04.2019

**Trade name: Zettex Zinc Spray Galvaniser**

(Contd. of page 1)

- **Signal word** Danger

- **Hazard-determining components of labelling:**

Acetone  
Hydrocarbons,C9,aromatics  
butanol

- **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

- **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe spray.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves / eye protection.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
  
P403 Store in a well-ventilated place.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Active substance with propellant

- **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	25-<50%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 128601-23-0 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons,C9,aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	2.5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas (Comp.), H280	2.5-<10%

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 30.04.2019

Version: 30

Revision: 30.04.2019

**Trade name: Zettex Zinc Spray Galvaniser**

(Contd. of page 2)

CAS: 7440-66-6 EINECS: 231-175-3 Reg.nr.: 01-2119467174-37	zinc powder -zinc dust (stabilized) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-<2.5%
CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38	butanol Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-<2.5%
CAS: 1174522-09-8 EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons,C10-C13,n-alkanes,cyclic,<2%aromates, Benzene <0.1% Asp. Tox. 1, H304	0.1-<1%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119463881-32	trizinc bis(orthophosphate) Aquatic Chronic 1, H410	≥0.25-<1%
CAS: 1314-13-2 EINECS: 215-222-5 Reg.nr.: 01-2119463881-32	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.1-<0.25%

· **Additional information:**

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
Water haze  
Fire-extinguishing powder  
Carbon dioxide  
Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 30.04.2019

Version: 30

Revision: 30.04.2019

**Trade name: Zettex Zinc Spray Galvaniser**

(Contd. of page 3)

Do not flush with water or aqueous cleansing agents

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

- **Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- **Information about storage in one common storage facility:**

Observe official regulations on storing packagings with pressurised containers.

- **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

**67-64-1 Acetone**
WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppmLong-term value: 1210 mg/m<sup>3</sup>, 500 ppm
**106-97-8 butane (containing < 0.1 % butadiene (203-450-8))**
WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppmLong-term value: 1450 mg/m<sup>3</sup>, 600 ppm

Carc (if more than 0.1 % of buta-1.3-diene)

**74-98-6 propane**
WEL Long-term value: 1800 mg/m<sup>3</sup>
**75-28-5 isobutane (containing < 0,1 % butadiene (203-450-8))**
WEL Short-term value: 2400 mg/m<sup>3</sup>Long-term value: 1900 mg/m<sup>3</sup>
**71-36-3 butanol**
WEL Short-term value: 154 mg/m<sup>3</sup>, 50 ppm

Sk

**1174522-09-8 Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%**
OEL Short-term value: 1200 mg/m<sup>3</sup>, 184 ppm

(Contd. on page 5)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 30.04.2019

Version: 30

Revision: 30.04.2019

**Trade name: Zettex Zinc Spray Galvaniser**

(Contd. of page 4)

· DNELs		
<b>67-64-1 Acetone</b>		
Oral	DNEL Long term-systemic	62 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	62 mg/kg bw/day (Consumer)
Inhalative		186 mg/kg bw/day (Worker)
	DNEL Acute-local	2420 mg/m <sup>3</sup> (Worker)
	DNEL Long term-systemic	200 mg/m <sup>3</sup> (Consumer)
		1210 mg/m <sup>3</sup> (Worker)
<b>128601-23-0 Hydrocarbons,C9,aromatics</b>		
Oral	DNEL Long term-systemic	11 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	11 mg/kg bw/day (Consumer)
Inhalative		25 mg/kg bw/day (Worker)
	DNEL Long term-systemic	32 mg/m <sup>3</sup> (Consumer)
		100 mg/m <sup>3</sup> (Worker)
<b>7440-66-6 zinc powder -zinc dust (stabilized)</b>		
Oral	DNEL Long term-systemic	50 mg/kg bw/day (Worker)
Dermal	DNEL Long term-systemic	5000 mg/kg bw/day (Consumer)
Inhalative		5000 mg/kg bw/day (Worker)
	DNEL Long term-systemic	2.5 mg/m <sup>3</sup> (Consumer)
		5 mg/m <sup>3</sup> (Worker)
<b>71-36-3 butanol</b>		
Oral	DNEL Long term-systemic	3.125 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-local	310 mg/m <sup>3</sup> (Consumer)
		55 mg/m <sup>3</sup> (Worker)

· PNECs		
<b>67-64-1 Acetone</b>		
PNEC Marine water		1.06 mg/l (Undefined)
PNEC Freshwater sediment		30.4 mg/l(dry weight) (Undefined)
PNEC Soil		29.5 (Undefined)
PNEC Marine water sediment		3.04 mg/l(dry weight) (Undefined)
<b>7440-66-6 zinc powder -zinc dust (stabilized)</b>		
PNEC Freshwater		20.6 mg/l (Undefined)
PNEC Marine water		6.1 mg/l (Undefined)
PNEC Freshwater sediment		118 mg/l(dry weight) (Undefined)
PNEC Soil		56.6 (Undefined)
PNEC Sewage Treatment Plant		52 mg/l (Undefined)
PNEC Marine water sediment		56.5 mg/l(dry weight) (Undefined)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 30.04.2019

Version: 30

Revision: 30.04.2019

**Trade name: Zettex Zinc Spray Galvaniser**

(Contd. of page 5)

**· Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2P2

**· Protection of hands:**

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.5$  mm
**· Penetration time of glove material**

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye protection:**

Safety glasses



Tightly sealed goggles

**· Body protection:** Use protective suit. (EN-13034/6)

### SECTION 9: Physical and chemical properties

**· 9.1 Information on basic physical and chemical properties**
**· General Information**
**· Appearance:**

<b>Form:</b>	Aerosol
<b>Colour:</b>	According to product specification
<b>· Odour:</b>	Characteristic
<b>· Odour threshold:</b>	Not determined.

**· pH-value:** Not determined.

**· Change in condition**

<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	-44.5 °C

**· Flash point:** -97 °C

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 30.04.2019

Version: 30

Revision: 30.04.2019

Trade name: Zettex Zinc Spray Galvaniser

(Contd. of page 6)

· <b>Flammability (solid, gas):</b>	Not applicable.
· <b>Auto-ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible. Not determined.
· <b>Explosion limits:</b>	
<b>Lower:</b>	0.7 Vol %
<b>Upper:</b>	13 Vol %
· <b>Vapour pressure at 20 °C:</b>	4 hPa
· <b>Density at 20 °C:</b>	0.711 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	89.4 %
<b>Solids content:</b>	7.4 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

##### 67-64-1 Acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	7800 mg/kg (rbt)
Inhalative	LC50/4h	>20 mg/l (rat)

##### 128601-23-0 Hydrocarbons,C9,aromatics

Oral	LD50	3492 mg/kg (rat)
Dermal	LD50	>3160 mg/kg (rabbit)
Inhalative	LC50/4 h	>6193 mg/l (rat) (Acute Inhalation Toxicity)

(Contd. on page 8)

GB



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 30.04.2019

Version: 30

Revision: 30.04.2019

**Trade name: Zettex Zinc Spray Galvaniser**

(Contd. of page 7)

**7440-66-6 zinc powder -zinc dust (stabilized)**

Oral	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4h	>5.4 mg/l (rat)

**71-36-3 butanol**

Oral	LD50	2292 mg/kg (rat)
Dermal	LD50	3430 mg/kg (rbt)
Inhalative	LC50/4 h	>17.76 mg/l (rat)

**7779-90-0 trizinc bis(orthophosphate)**

Oral	LD50	5000 mg/kg (rat)
------	------	------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**
**12.1 Toxicity**
**Aquatic toxicity:**
**67-64-1 Acetone**

EC50	8800 mg/l (Daphnia magna)
	8300 mg/l (Fish)

**128601-23-0 Hydrocarbons,C9,aromatics**

NOELR (72h)	1 mg/l (Pseudokirchneriella subcapitata)
EL50(48h)	3.2 mg/l (Daphnia magna)
LL50 (96h)	9.2 mg/l (Oncorhynchus mykiss (96h))

**7440-66-6 zinc powder -zinc dust (stabilized)**

EC50	354 ug/l (Daphnia Magna 48h)
NOEC/21d	178 ug/l (Crustaceen-Palaemon elegans)
NOEC (72h)	9 mg/l (Ceratophyllum demersum)
	0.017 mg/l (Pseudokirchneriella subcapitata)
NOEC/72h	72.9 ug/l (Pseudokirchneriella subcapitata)
NOEC/4w	8.3 ug/l (Cyprinus carpio)
EC10/21d	59.2 ug/l (Daphnia magna)
EC10/72h	27.3 ug/l (algae)
EC50 (72h)	0.17 mg/l (Selenastrum capricornatum (72 h))
LC50/96h	0.41 mg/l (Oncorhynchus mykiss)
EC50/48h	1 mg/l (Daphnia magna)
EC50/96h	0.527 mg/l (algae)
LC50	238-269 ug/l (Pimephales promelas (96 h))

(Contd. on page 9)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 30.04.2019

Version: 30

Revision: 30.04.2019

**Trade name: Zettex Zinc Spray Galvaniser**

(Contd. of page 8)

**71-36-3 butanol**

NOEC (21 days)	4.1 mg/l (Daphnia magna)
LC50/96h	1376 mg/l (Pimephales promelas)
EC50/48h	1328 mg/l (Daphnia magna)
EC50	225 mg/l (Selenastrum capricornatum (72 h))

**7779-90-0 trizinc bis(orthophosphate)**

LC50/96h	0.14 mg/l (Oncorhynchus mykiss (96h))
EC50/48h	2.34 mg/l (Daphnia magna)
ErC(50) (72h)	0.14 mg/l (Desmodesmus subspicatus)

- **12.2 Persistence and degradability** Easily biodegradable
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

- **14.1 UN-Number**
- **ADR, ADN, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR, ADN** UN1950 AEROSOLS
- **IMDG** AEROSOLS (zinc powder -zinc dust (stabilized), Solvent naphtha (petroleum), light arom. Benzene<0.1%, trizinc bis(orthophosphate), zinc oxide), MARINE POLLUTANT
- **IATA** AEROSOLS, flammable

(Contd. on page 10)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 30.04.2019

Version: 30

Revision: 30.04.2019

Trade name: Zettex Zinc Spray Galvaniser

(Contd. of page 9)

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 2.5F Gases.  
 · **Label** 2.1

· **ADN**

· **ADN/R Class:** 2.5F

· **IMDG**



· **Class** 2.1  
 · **Label** 2.1

· **IATA**



· **Class** 2.1  
 · **Label** 2.1

· **14.4 Packing group**

· **ADR, IMDG, IATA** Void

· **14.5 Environmental hazards:**

Product contains environmentally hazardous substances:  
 zinc powder -zinc dust (stabilized)

· **Marine pollutant:**

Yes  
 Symbol (fish and tree)

· **Special marking (ADR):**

Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Gases.

· **Danger code (Kemler):**

-

· **EMS Number:**

F-D,S-U

· **Stowage Code**

SW1 Protected from sources of heat.  
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· **Segregation Code**

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 1L

(Contd. on page 11)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 30.04.2019

Version: 30

Revision: 30.04.2019

**Trade name: Zettex Zinc Spray Galvaniser**

(Contd. of page 10)

· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
P3a FLAMMABLE AEROSOLS  
E2 Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**

Class	Share in %
NK	75-<100
- **VOC-CH** 89.30 %
- **VOC-EU** 635.6 g/l
- **Danish MAL Code** 5-6
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.
- **Department issuing SDS:**  
Produktsicherheit  
Research & Development

(Contd. on page 12)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 30.04.2019

Version: 30

Revision: 30.04.2019

**Trade name: Zettex Zinc Spray Galvaniser**

(Contd. of page 11)

· **Contact:**

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

GB