



STICK WITH US

## TECHNICAL DATA SHEET Easy Silicone Acetoxy GP



### Zettex Europe BV

Partridgeweg 1, 4791 RV Klundert

The Netherlands

+31 (0)888-93 88 39

[info@zettex.com](mailto:info@zettex.com)

[www.zettex.com](http://www.zettex.com)

### Product Description

Zettex Easy Silicone Acetoxy General Purpose is an acetic acid-containing universal silicone sealant for all connection joints used in construction and industry.

### Material

Acetic acid.

### Advantages

- Insensitive to mold.
- Chemical resistant.
- Colourfast.
- Permanently elastic.
- UV resistance.
- Excellent workability.
- (sea) water resistant.

### Applications

For sealing joints, seams and cracks in all materials used in construction, such as connection joints and edge seals in floors, facades, glazing, container construction, cold stores and air circulation systems.

### Utilization

The surface must be clean, dry and free of dust and grease. Clean the surface in advance with Zettex Profi Cleaner. Any uncured sealant residue and other dirty material can be removed with Zettex Profi Cleaner. Smooth finish with Zettex Easy Finish. Always test the surface for adhesion in advance. After use, hands can be cleaned with Zettex Cleaning Wipes.

### Packaging

- Cartridge 310 ml

### Colour

White, black, grey, transparent, Other colours are available on request.

### Safety recommendations

Always read the safety information before use.

### Shelf life

18 months in unopened packaging. Store at temperatures between 5°C and 25°C.

Properties	Specifications
Basic	Acetoxy

Hardening	2 mm per 24 hours
Processing temperature	+5°C to +40°C
UV resistance	Very good
Skin formation time	Approx. 5 minutes
Temperature resistance (cured)	-50°C to +180°C
Water resistance	excellent
Density	1.00g/ml
Elongation at break	500%
Tensile strength	1.25N/mm <sup>2</sup>
Shore A hardness	24