



## **TECHNICAL DATA SHEET**

# **Easy Silicone Acetoxy Sanitary**

#### **Zettex Europe BV**

www.zettex.com

Partridgeweg 1, 4791 RV Klundert The Netherlands +31 (0)888-93 88 39 info@zettex.com

### **Product Description**

Zettex Easy Silicone Acetoxy Sanitary is a high-quality one-component mold-resistant sealant based on Acetoxy (acetic acid). Properties: Permanently soft and elastic. Perfectly resistant to mold and bacteria. High UV resistance. Not paintable . Durable and colorfast.

#### Material

Acetic acid.

### **Advantages**

- · Insensitive to mold.
- · Chemical resistant.
- · Colourfast.
- Permanently elastic.
- UV resistance.
- · Excellent workability.
- (sea) water resistant.

### **Applications**

For sealing all types of joints in sanitary areas and kitchens. Due to its wide range of applications, it is the perfect all-rounder. rounder .

### **Processing**

The surface must be clean, dry and free of dust and grease. Clean the surface in advance with Zettex Profi Cleaner. Any uncured sealant residue and other dirty material can be removed with Zettex Profi Cleaner . Smooth finish with Zettex Easy Finish. Always test the surface for adhesion in advance. After use, hands can be cleaned with Zettex Cleaning Wipes .

### **Packaging**

• Cartridge 310 ml

#### Colour

White, black, grey, anthracite, transparent, transparent grey, ral 9001. Other colours are available on request.

### Safety recommendations

Always read the safety information before use.

#### Shelf life

18 months in unopened packaging. Store at temperatures between 5°C and 25°C.

Properties	Specifications

Base	Acetoxy
Hardening	2 mm per 24 hours
Processing temperature	+5°C to +40°C
UV resistance	Very good
Skin formation time	Approx. 5 minutes
Temperature resistance (cured)	-50°C to +180°C
Water resistance	excellent
Density	1.00g/ml
Elongation at break	600%
Tensile strength	1.25N/mm²
Shore A hardness	24